

BANDVULC

WASTEMASTER

Master the environment with **ARMORBAND™** technology

**ENGINEERED FOR ENDURANCE
AND RESILIENCE, NO MATTER
THE CONDITIONS**



THE NEXT GENERATION **WASTE TYRE** IS HERE

Bandvulc's **WASTEMASTER** tyre range has been specifically engineered with bespoke features for maximising tyre life and resisting service damage in regional and urban waste and recycling environments. Its pioneering ARMORBAND™ technology provides resistance to impacts and kerbing and Bandvulc's exclusive rubber compound and tread design features offer exceptional performance and handling characteristics no matter the conditions.



For more technical information on the **WASTEMASTER** range and all things Bandvulc, visit us online today at...

BANDVULC.COM



BANDVULC



WASTEMASTER 5

295/80R22.5 | 315/80R22.5

The **WM5** provides resilience and performance combining Bandvulc's ARMORBAND™ sidewall protection technology with a bespoke tread design incorporating wide zig zag grooves for excellent displacement of mud and water, stone ejection features and a solid shoulder design for enhanced stability control. Certified with 3PMSF accreditation the **WM5** offers excellent traction, grip in severe conditions and reliable handling.

ARMORBAND™ WITH VISUAL INDICATOR

Provides an additional safety barrier against kerbing; a coloured internal strip of rubber provides an early warning in the event the barrier is compromised.



KEY FEATURE HANDLING ASSIST

The solid shoulder design and wide contact area promotes steering control and combats lateral forces. Stepped tread blocks and additional deep sipes provide excellent traction and grip in severe conditions.



STONE EJECTION features within the tread grooves prevent stone trapping and drills.

ALSO AVAILABLE IN HIGH LOAD

The **295/80R22.5** size offers a higher load index (154/149 J) where required for certain applications.



3PMSF ACCREDITATION

The tyre meets the required performance criteria in snow testing and provides improved snow traction and all weather performance beyond a standard M+S branded tyre.

Tyre Size	295/80R22.5	315/80R22.5
Tread Pattern	WM5	WM5
Load Index	152/148	156/150
Speed Symbol	J	J
Speed Km/h	100	100
Recommended Rim	8.25	9
Fitment	All Round	All Round
Max inflation Pressure:		
Bar	8.5	8.5
PSI	123	123
Features	ABV, SE, HA	ABV, SE, HA

ARMORBAND™



WASTEMASTER II

10R22.5 | 11R22.5 | 295/80R22.5 | 315/80R22.5

The robust, urban features of the **WMII** are optimised for outstanding tyre longevity. Bandvulc's bespoke high polymer compound with high levels of natural rubber provides superior tear and puncture resistance teamed with ARMORBAND™ sidewall protection to provide an extra barrier against kerbing and a visual indicator. The High Load version is purpose-designed for the latest generation of original equipment.

KEY FEATURE ARMORBAND™ + VISUAL INDICATOR

Extra protection around the sidewall of the tyre provides an additional safety barrier against kerbing and sidewall damage. A coloured internal strip provides an early warning in the event the ARMORBAND™ barrier is compromised and the tyre is being excessively worn on the sidewall.



HIGH POLYMER
rubber provides excellent resistance to harsh driving conditions.



HIGH LOAD
Provides a higher load index (154/149) where required for certain applications (Available in 295/80R22.5)

Tyre Size	10R22.5	11R22.5	295/80R22.5	315/80R22.5
Tread Pattern	WMII	WMII	WMII	WMII
Load Index	144/142	148/145	152/148	156/150
Speed Symbol	J	J	J	J
Speed Km/h	100	100	100	100
Recommended Rim	6.75	7.50	8.25	9.00
Fitment	All Round	All Round	All Round	All Round
Max inflation Pressure:				
Bar	8.5	8.5	8.5	8.5
PSI	123	123	123	123
Features	ABV, HP	ABV, HP	ABV, HP	ABV, HP

**ALSO
AVAILABLE IN
HIGH LOAD**
295/80R22.5

BANDVULC




WASTEMASTER III

315/70R22.5

A proven, versatile application in regional and urban environments. The **WMIII** includes Bandvulc's ARMORBAND™ with visual indicator, a solid shoulder for improved grip when cornering along with a tread design to maximise traction. Suitable for high mileage, urban applications.

ARMORBAND™ WITH VISUAL INDICATOR

Extra protection around the sidewall of the tyre provides an additional safety barrier against kerbing and sidewall damage. A coloured internal strip provides an early warning in the event the ARMORBAND™ barrier is compromised and the tyre is being excessively worn on the sidewall.



HIGH POLYMER
rubber provides excellent resistance to harsh driving conditions.



KEY FEATURE ADVANCED MILEAGE

The tread design enables good contact with the road for enhanced grip and footprint, a better pence per kilometre and reduces energy loss.



Tyre Size	315/70R22.5
Tread Pattern	MKIII WM
Load Index	154/150
Speed Symbol	J
Speed Km/h	110
Recommended Rim	9.00
Fitment	All Round
Max inflation Pressure:	
Bar	9.0
PSI	131
Features	ABV, HP, AM

MASTER THE ENVIRONMENT WITH **ARMORBAND™** TECHNOLOGY

Bandvulc's **ARMORBAND™** technology provides an additional protective layer of rubber compound on the mid to lower sidewall of the tyre. This tapered protective band adds additional protection against sidewall scrubbing which can otherwise lead to premature tyre removal. The visual indicator is made up of a coloured internal strip, which offers a clear, unmistakable warning if the barrier is compromised by the tyre being excessively worn or damaged on the sidewall.



ARMORBAND™ at work, providing an extra layer of protection against excessive sidewall damage



TYRES ENGINEERED & MANUFACTURED IN THE UK

WHY BANDVULC?

INNOVATION **INDUSTRY LEADING PROCESSES, DESIGN AND TECHNOLOGY**

We continually invest in the future of our purpose-built LifeCycle plant by taking full advantage of technical advances and the latest technology available throughout the retreading operation. Our pioneering approach allows us to combine hot and cold retreading under one roof in a closed production cycle where synergies from retreading and rubber recycling are used enabling us to set new standards in sustainability.

EXPERTISE **50 YEARS OF RESEARCH, INVESTMENT AND TEAMWORK**

People are the driving force behind our success. Across the business we have experts in rubber technology, research and development, robotics and engineering allowing us to design a unique range of tyres for specific applications, right down to the bespoke rubber compounds produced in-house in our laboratory.

Our extensive knowledge of UK roads and ongoing investment into in-house rubber technology enables us to engineer products and compounds to suit a wide variety of uses and applications.

Bandvulc manufacture a tyre every 3 minutes, each one quality assured and with bespoke features designed to perform for our customers whatever the challenge.

QUALITY **SETTING THE RETREAD STANDARD**

From initial design and development work to casing recycling and tread application, we implement critical quality control measures across our business that ensure we operate in the most efficient way and continually improve in all respects to fulfil our standards and achieve the best retread tyre.

SUSTAINABILITY **A GREENER JOURNEY AND EXTENDED LIFE CYCLES**

Since the beginning we have been committed to the care of the environment, prevention of pollution and our responsibility to ensure that our retreading operation is as efficient as possible with minimum impact to the environment. This not only includes the manufacturing processes in place and our zero-to- landfill policy but also through our diverse product offering and the quality retreads we provide for customers. Sustainability has, and always will be at the heart of our operations, across the board.

BANDVULC

RESILIENCE MEETS PERFORMANCE.



BANDVULC.COM
A BRAND OF CONTINENTAL



Bandvulc Tyres Ltd
Gillard Way, Lee Mill Industrial Estate
Ivybridge, Devon, PL21 9LN
Tel: 01752 429198

Follow us on...

